


UNI
BLOCK

Thermal Insulated Modular System


A modern method of construction

- ❑ Insulating Concrete Formwork (ICF)
- ❑ Suitable for residential, commercial, industrial & institutional construction
- ❑ 600mm high x 2400mm long
- ❑ Inner leaf of 75mm & outer leaf of 75mm, 110mm or 150mm Neopor® Polystyrene
- ❑ Embedded wire mesh with a patented folding mechanism



Technical specification

- ❑ Fire rating EN 1365-1:2000 and classified as REI 130
- ❑ Air tightness typical build 0.73m³/hr/m²
- ❑ Sound insulation 50 dB
- ❑ Flood resistance neither concrete nor expanded polystyrene rot or suffer from water damage



Panel thickness	75mm	110mm	150mm
Weight per block	15 kg	16 kg	18Kg
U value	0.22 w/m ² k	0.19 w/m ²	0.16 w/m ²
Part number	UN7575	UN75110	UN75150

In partnership with global construction expertise & scale



UK & Ireland distributor for Polycrete –
25 year old Canadian manufacturer of
Insulating Concrete Formwork



Manufactured by Glava, the leading Scandinavian
insulation supplier, just acquired by Saint Gobain,
the €41 billion global construction giant




UK & Ireland partner for Cemex



Cavalok frames by Eurocell
can be used as part of the build system


Lower build cost

- ❑ Fast construction
- ❑ Low labour cost utilising an alternative skills set
- ❑ Training completed within 3 days
- ❑ Can be cut in advance off-site with Express Wall or near-site.
- ❑ Just in time delivery enhancing site discipline and cleanliness
- ❑ We estimate that using ICF in its pre-cut form can produce savings of between 20-30% on site.
- ❑ Built in Quality simple to follow instructions



Sustainability using ICF

- ❑ Comparing ICF to other building materials, life-cycle assessments show that they outperform these in nearly every region and type of construction.
- ❑ A building's effect on the environment over its lifetime shows that the everyday use including heating and cooling is the biggest impact.
- ❑ UNiBLOCK's ability to combine in-situ concrete walls with permanent EPS formwork maximises airtightness and thermal efficiency, resulting in significantly reduced energy & environmental costs and longer life expectancy.



UNI
BLOCK

A typical build


Simple to use on site

- ❑ Light weight and easy to handle
- ❑ Help in the reduction of handling injuries at site level



Base track

- ❑ Shot-fired into the slab or foundation
- ❑ Keeping the wall plumb during first row placement




First course

- ❑ Setting out of first course as per the designed plan from UNiBLOCK
- ❑ Blocks are numbered for ease of placement



Locking together

- ❑ Each block is locked together with the next adjacent block using a simple metal clip to hold them in place.
- ❑ The internal metal cages are connected resulting in a secure and stable shuttering system ready for the concrete to be poured.



Platform systems

- ❑ As each wall gains height, a working platform and bracing system is attached to keep the wall plumb during placement



Doors & windows pre-framed

- ❑ As each wall is designed and cut offsite, placement of windows and doors is simplified



Concrete placement

- ❑ Pump mix concrete is placed using a boom pump, or smaller line pump where practical.
- ❑ Typical concrete specification: C25/C30 10mm aggregate with S3 slump.



A range of finishes



Unit 5-7 Queensway Industrial Estate
Dunlop Way
Scunthorpe
DN16 3RN

Tel: 0333 355 6879

www.uniblock.co.uk

UNI
BLOCK

Contact info.

james@uniblock.co.uk

07585 562835

